



## VERANCE-S

### Technical Specifications | Teknik Özellikler

Body	: Electrostatic Powder Coated DKP Sheet Metal
Diffuser	: Opal Diffuser
Glass	: Tempered Glass
Light Source	: Mid Power LED
CRI	: Ra>80
Input Voltage	: 220-240V AC 50/60Hz
Body Color	: Ral 9016
Usage	: Recessed Ceiling
IP	: IP65

Gövde	: Elektrostatik Toz Boyalı DKP Sac
Reflektör	: Opal Difüzör
Cam	: Temperli Cam
Işık Kaynağı	: Mid Power LED
CRI	: Ra>80
Giriş Gerilimi	: 220-240V AC 50-60Hz
Gövde Rengi	: Ral 9016
Kullanım Şekli	: Sıva Altı
IP	: IP65


### Product Chart | Ürün Tablosu

Product Code	Power	CCT/K	Lumen	Cut Out (mm)
SML211.303.40.00.15.40	15W	4000	1700	275X275
SML211.303.41.00.15.40	15W	4000	1700	275X275
SML211.303.42.00.15.40	15W	6500	1700	275X275
SML211.303.41.00.15.65	15W	6500	1700	275X275
SML211.303.40.00.15.65	15W	6500	1700	275X275
SML211.303.42.00.15.40	15W	6500	1700	275X275

### Options | Opsiyonlar

- DALI Compatible
- Emergency Unit (1-3 Hour)
- Suspended Ceiling Compatible : Plasterboard, Rockwool, Clip-in
- DALI Uyumlu
- Acil Durum Kit'i (1-3 Saat)
- Asma Tavan Uyumlu : Alçıpan, Taşyünü, Clip-in

### Dimensions | Ölçüler



a:295mm / b:295mm / h:75mm

### Photometric Data | Fotometrik Veri

