

VERANCE-M

Technical Specifications | Teknik Özellikler

Body	: Electrostatic Powder Coated DKP Sheet Metal
Diffuser	: Opal Diffuser
Glass	: Tempered Glass
Light Source	: Mid Power LED
CRI	: Ra>80
Input Voltage	: 220-240V AC 50/60Hz
Body Color	: Ral 9016
Usage	: Surface Mounted Ceiling
IP	: IP65


Gövde	: Elektrostatik Toz Boyalı DKP Sac
Reflektör	: Opal Difüzör
Cam	: Temperli Cam
Işık Kaynağı	: Mid Power LED
CRI	: Ra>80
Giriş Gerilimi	: 220-240V AC 50-60Hz
Gövde Rengi	: Ral 9016
Kullanım Şekli	: Sıva Üstü
IP	: IP65

Options | Opsiyonlar

DALI Compatible
Emergency Unit (1-3 Hour)

DALI Uyumlu
Acil Durum Kit'i (1-3 Saat)

Dimensions | Ölçüler



a:315mm / b:3315mm / h:75mm

Product Chart | Ürün Tablosu

Product Code	Power	CCT/K	Lumen
SML221.303.43.00.15.40	15W	4000	1700
SML221.303.43.00.15.65	15W	6500	1700

Photometric Data | Fotometrik Veri

