



CLASS

Technical Specifications | Teknik Özellikler

Body	: Polycarbonate Body
Diffuser	: Polycarbonate Glass Cover
Light Source	: TLD Fluorescent Lamp
Ballast	: Electronic Ballast
Input Voltage	: 220-240V AC 50/60Hz
Body Color	: Ral 9006
Usage	: Surface Mounted
IP	: IP65

Gövde	: Polikarbon Gövde
Difüzör	: Polikarbon Cam Kapak
Işık Kaynağı	: TLD Floresan Lamba
Balast	: Elektronik Balast
Giriş Gerilimi	: 220-240V AC 50-60Hz
Gövde Rengi	: Ral 9006
Kullanım Şekli	: Sıva Üstü
IP	: IP65

Options | Opsiyonlar

Emergency Unit (1-3 Hour)

Acil Durum Kit'i (1-3 Saat)

Product Chart | Ürün Tablosu

Product Code	Power	LAMP	a / b / c
SMF 141.118 U1	1x18W	TLD FLUORESCENT	660x80x80
SMF 141.218 U1	2x18W	TLD FLUORESCENT	660x140x80
SMF 141.136 U1	1x36W	TLD FLUORESCENT	1260x80x80
SMF 141.236 U1	2x36W	TLD FLUORESCENT	1260x140x80
SMF 141.158 U1	1x58W	TLD FLUORESCENT	1560x80x80
SMF 141.258 U1	2x58W	TLD FLUORESCENT	1560x140x80
SMF 141.118 U1 L	1x18W	TLD LED TUBE	660x80x80
SMF 141.218 U1 L	2x18W	TLD LED TUBE	660x140x80
SMF 141.136 U1 L	1x36W	TLD LED TUBE	1260x80x80
SMF 141.236 U1 L	2x36W	TLD LED TUBE	1260x140x80
SMF 141.158 U1 L	1x58W	TLD LED TUBE	1560x80x80
SMF 141.258 U1 L	2x58W	TLD LED TUBE	1560x140x80

Dimensions | Ölçüler

