

LUMOS

Technical Specifications | Teknik Özellikler

Body	: Aluminium
Diffuser	: Opal Diffuser
Light Source	: Mid Power LED
CRI	: Ra>80
Input Voltage	: 220-240V AC 50/60Hz
Body Color	: Ral 9005 / Optional
Usage	: Pendant / Surface Mounted
IP	: IP20 / IP40

Gövde	: Alüminyum
Lens	: Opal Difüzör
Isık Kaynağı	: Mid Power LED
CRI	: Ra>80
Giris Gerilimi	: 220-240V AC 50/60Hz
Gövde Rengi	: Ral 9005 / Opsiyonel
Kullanım Şekli	: Sarkit / Sıva Üstü
IP	: IP20 / IP40

Product Chart | Ürün Tablosu

Product Code	Power	CCT/K	Lumen
SML640.030.V14.00.18.30	18W	3000	1800
SML640.060.V14.00.36.30	36W	3000	3600
SML640.090.V14.00.54.30	54W	3000	5400
SML640.120.V14.00.72.30	72W	3000	7200
SML640.030.V14.00.18.40	18W	4000	1950
SML640.060.V14.00.36.40	36W	4000	3900
SML640.090.V14.00.54.40	54W	4000	5850
SML640.120.V14.00.72.40	72W	4000	7800



Options | Opsiyonlar

DALI Compatible
Emergency Unit (1-3 Hour)

DALI Uyumlu
Acil Durum Kit'i (1-3 Saat)

It Can Be Produced in Desired Sizes and
in Different Combinations.
İstenilen Ölçülerde ve Farklı Kombinasyonlarda
Üretilir.

Dimensions | Ölçüler

