

NEBULUS

Technical Specifications | Teknik Özellikler

Body	: Aluminium
Diffuser	: Opal Diffuser
Light Source	: Mid Power LED
CRI	: Ra>80
Input Voltage	: 220-240V AC 50/60Hz
Body Color	: Ral 9005 / Optional
Usage	: Pendant
IP	: IP20 / IP40

Gövde	: Alüminyum
Lens	: Opal Difüzör
Isık Kaynagi	: Mid Power LED
CRI	: Ra>80
Giris Gerilimi	: 220-240V AC 50/60Hz
Gövde Rengi	: Ral 9005 / Opsiyonel
Kullanım Şekli	: Sarkıt
IP	: IP20 / IP40

Product Chart | Ürün Tablosu

Product Code	Power	CCT/K	Lumen	L mm
SML670.400.V14.00.100.30	100W	3000	10000	1000*1000*1000*1000
SML670.400.V14.00.100.40	100W	4000	10500	1000*1000*1000*1000
SML670.400.V14.00.100.65	100W	6500	10500	1000*1000*1000*1000



Options | Opsiyonlar

DALI Compatible
Emergency Unit (1-3 Hour)

DALI Uyumlu
Acil Durum Kit'i (1-3 Saat)

It Can Be Produced in Desired Sizes and
in Different Combinations.
İstenilen Ölçülerde ve Farklı Kombinasyonlarda
Üretilebilir.

Dimensions | Ölçüler

